This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**



Claim 1 (Currently amended): A portable seat assembly for use by a person bathing, the seat assembly comprising:

a horizontal <u>sitting</u> surface constructed of a rigid material, said horizontal surface being unattached to any flooring or wall;

a first support, said first support including a first leg, a second leg, and a first brace support connecting the first leg to the second leg, the first leg and second leg being unattached to any flooring or wall;

a second support, said second support including a third leg, a fourth leg and a second brace support connecting the third leg to the fourth leg, the third leg and fourth leg being unattached to any flooring or wall;

the first brace support affixed to an underside of said horizontal surface;

the second brace support diagonally laying across the first brace support on the underside of said horizontal surface;

a basket slidably mounted to the underside of said horizontal surface, said basket having:

a generally horizontal bottom surface;

four generally vertical sides affixed to the bottom surface, the four sides and bottom surface forming an enclosure for storing shower supplies; and

two overhanging edges extending outwardly from a top portion of two opposing sides of said basket; and

PATENT APPLICATION DOCKET NO. 1238-0006

means for slidably supporting the two overhanging edges of said basket on the underside of said horizontal surface;

whereby said basket may be slid <u>horizontally</u> outwardly either fore or aft from said horizontal surface and the person may sit on said horizontal surface.

Claim 2 (Original): The seat assembly of claim 1, wherein the means for slidably supporting the two overhanging edges of said basket is two guide rails mounted on the underside of said horizontal surface, each guide rail forming a lip to support each overhanging edge of said basket.

Claim 3 (Original): The seat assembly of claim 2 wherein each guide rail is affixed to the first and second brace supports to provide additional stability to the seat assembly.

Claim 4 (Original): The seat assembly of claim 1 further comprising means for affixing said basket to an edge of said horizontal surface.

Claim 5 (Original): The seat assembly of claim 4 wherein the means for affixing said basket to an edge of said horizontal surface is an adjustable rod affixed to the horizontal surface and extending from the edge of the horizontal surface to retain said basket against the edge of said horizontal surface.

## PATENT APPLICATION DOCKET NO. 1238-0006

Claim 6 (Original): The seat assembly of claim 1 wherein said horizontal surface includes a plurality of holes.

Claim 7 (Original): The seat assembly of claim 1 wherein said basket includes a plurality of apertures.

Claim 8 (Currently amended): A portable seat assembly for use by a person bathing, the seat assembly comprising:

a sitting horizontal surface constructed of a rigid material;

four support legs attached to an underside of said horizontal surface, said four support legs and horizontal surface being unattached to any flooring or wall;

a basket slidably mounted to the underside of said horizontal surface, said basket having:

a generally horizontal bottom surface;

four generally vertical sides affixed to the bottom surface, the four sides and bottom surface forming an enclosure for storing shower supplies; and

two overhanging edges extending outwardly from a top portion of two opposing sides of said basket; and

means for slidably supporting the two overhanging edges of said basket on the underside of said horizontal surface;

whereby said basket may be slid <u>horizontally</u> outwardly either fore or aft from said horizontal surface and the person may sit on said horizontal surface.

Eso,

Sint

Claim 9 (Original):

The seat assembly of claim 8 wherein:

a first support leg is attached to a second support leg to form a first support assembly; a third support leg is attached to a fourth support leg to form a second support assembly; whereby the first support assembly lies diagonally across the second support assembly.

Claim 10 (Original): The seat assembly of claim 8 wherein: said horizontal surface includes a plurality of holes; and said basket includes a plurality of apertures.

Claim 11 (Original): The seat assembly of claim 10 further comprising means for affixing said basket to an edge of said horizontal surface.

Claim 12 (Original): The seat assembly of claim 11 wherein the means for affixing said basket to an edge of said horizontal surface is an adjustable rod affixed through a hole of said horizontal surface and extending from the edge of said horizontal surface through an aperture of said basket to retain said basket against the edge of said horizontal surface.

Claim 13 (Original): The seat assembly of claim 8 further comprising a cover pivotably mounted to the underside of the horizontal surface.

Claim 14 (Previously amended): The seat assembly of claim 13 wherein the means for slidably supporting the two overhanging edges includes a plurality of outcroppings;

whereby said cover is tilted when said basket is slid outwardly from under said horizontal surface.

Claim 15 (Currently amended): A portable seat assembly for use by a person bathing, the seat assembly comprising:

a horizontal <u>sitting</u> surface constructed of a rigid material, said horizontal surface having a plurality of holes, said horizontal surface being unattached to any flooring or wall;

a first support, said first support including a first leg, a second leg, and a first brace support connecting the first leg to the second leg, the first and second leg being unattached to any flooring or wall;

a second support, said second support including a third leg, a fourth leg and a second brace support connecting the third leg to the fourth leg, the third <u>leg</u> and fourth leg being unattached to any flooring or wall;

the first brace support affixed to an underside of said horizontal surface;

the second brace support diagonally lying across the first brace support on the underside of said horizontal surface;

a basket slidably mounted to the underside of the horizontal surface, said basket having:

a generally horizontal bottom surface;

Blow

four generally vertical sides affixed to the bottom surface, the four sides and bottom surface forming an enclosure for storing shower supplies; and

two overhanging edges extending outwardly from a top portion of two opposing sides of said basket;

two guide rails mounted on the underside of the horizontal surface, each guide rail forming a lip to support each overhanging edge of said basket; and

an adjustable rod affixed to said horizontal surface and extending from the edge of said horizontal surface to retain said basket against the edge of said horizontal surface;

whereby said basket may be slid <u>horizontally</u> outwardly either fore or aft from said horizontal surface and the person may sit on said horizontal surface.

PATENT APPLICATION DOCKET NO. 1238-0006

## **Amendments to the Drawings:**

The attached sheet of drawings includes changes to FIG. 6. The changes to FIG. 6 have been approved by the Examiner in the current Office Action.

Attachment: Replacement Sheet